


# IG-118x96\_BRG48R Setup Instructions

## Show Labor Recommended




# Part 1: Setup Main Backwall


**1.)** Place frame flat on the floor paring like numbers. Assemble sides with small connector bars in outside channels & tighten screws. Be sure to connect Barrel Electrical Connectors at each respective joint.




**2.)** Assemble corners using corner brackets inserted into outside channels of frame. Tighten thumb screws.



**3.)** Assemble vertical support bars using large connector bar & tighten screw. Insert vertical bars in to marked location on frame.




**4.)** Install Horizontal support bars into to marked location on frame & tighten Tension Lock




• Turn Tension Lock to the right with T-30 tool to tighten lock into channel

**5.)** Assemble base plates to the bottom of the frame using the supplied bolts, washers, & wingnuts. Stand the frame up.




**6.)** Place SEG Graphic on the front and rear of the frame following the instructions on the last page of the instruction manual.




## Part 2: Setup Front Display

**1.)** Place frame flat on the floor paring like numbers. Assemble sides with small connector bars in outside channels & tighten screws. Be sure to connect Barrel Electrical Connectors at each respective joint.



**2.)** Assemble corners using corner brackets inserted into outside channels of frame. Tighten thumb screws.




**3.)** Install Monitor Bracket support bars into Front channel of frame and tighten Tension Lock



• Turn Tension Lock to the right with T-30 tool to tighten lock into channel



**4.)** Assemble base plates to the bottom of the frame using the supplied bolts, washers, and wingnuts. Stand the frame up.




**5.)** Place SEG Graphic on the front of the frame following the instructions on the last page of the instruction manual.

**6.)** Adjust TV Bracket if necessary to align with slits in the front graphic. Place SEG Graphic on the Back of the frame following the instructions on the last page of the instruction manual.


## Part 2: Setup Front Display

7.) Install side support feet on onto side of frame by inserting the T-Bolt into the center groove and tighten the knurled thumb screw.

**NOTE: FOR STABILITY SIDE SUPPORT FEET MUST BE IN PLACE UNLESS USING IN A BRIDGE CONFIGURATION.**



8.) **OPTIONAL SHELF:** Install a side shelf bracket on each side by inserting the T-Bolts into the center groove and tighten the knurled thumb screw.




Install the shelf assembly by setting it on the shelf Brackets. **NOTE: Do not disassemble the support bar from the shelf.**




## Part 3: Setup Bridge

**1.)** Place frame flat on the floor paring like numbers. Assemble sides with large center connector bar & small connector bars in center & outside channels respectively & tighten screws. Be sure to connect Barrel Electrical Connectors at each respective joint.






• Small connector bars



• Large connector bar

**2.)** Assemble corners using corner brackets inserted into outside channels of frame. Tighten thumb screws.




**3.)** Install Horizontal support bars into to marked location on frame and tighten Tension Lock



- Turn Tension Lock to the right with T-30 tool to tighten lock into channel

**4.)** Attach Bridge brackets to the short side of frame using the provided thumb screws. Thumb screws should be placed in the outer holes of the bracket.




**6.)** Place SEG Graphic on the front and rear of the frame following the instructions on the last page of the instruction manual.

## Part 4: Arrange Displays

**1.)** Place fully assembled Backwall into desired location at the rear of the booth space.

**2.)** Measure out approximately 90" from the front of the Backwall and place Front Display into desired location at the front of the booth space.

**3.)** Using two people, lift the Fully Assembled Bridge Display so that the brackets rest on the Backwall on one side and on the front display on the other. Secure the Bridge by inserting the T-bolts into the groove on the Backwall and Front Display and tighten to secure.



• Insert T-Bolt into groove and secure by tightening thumb screw

